Components Group

Bending: dual

IP 67

CRI 90

Lifespan: ≥ 50 000 h


Warranty: 5 years

Neon Flex Series

Neon Flex

Dual 10

Dual 10 is a modern Neon Flex with a vertical bending line, designed for applications requiring a continuous, uniform line of light and high color accuracy. Equipped with SMD 2216 LEDs with a CRI of 90, it delivers natural, even illumination in 3000 K, 4000 K, and 6000 K color temperatures. With a power rating of 8 W/m and an IP67 protection class, it ensures durability, weather resistance, and easy installation. Dual 10 combines aesthetics, flexibility, and reliability, making it an ideal solution for contemporary architectural and decorative lighting projects.



Product code	Light type	Colour temp.	LED type	Voltage	Power/m	Beam angle	Luminous flux	LEDs per meter	Cutting section	Bending radius
01-002-107-02-67	MONO	3000 K	SMD 2216	24 V DC	8 W	120°	414 lm	240 LED/m	Freely	60 mm
01-002-107-04-67	MONO	4000 K	SMD 2216	24 V DC	8 W	120°	450 lm	240 LED/m	Freely	60 mm
01-002-107-03-67	MONO	6000 K	SMD 2216	24 V DC	8 W	120°	441 lm	240 LED/m	Freely	60 mm

Double-sided mounting tape: **no**

Housing color: **white**

Light emission direction: **front**

Roll length: **10 m**

Maximum power supply length: **5 m**